

Newly upgraded 90kv



Integrated design

compact appearance  
Light structure



clear imaging

High efficiency



small in size

Light in weight  
Easy to operate



Low radiation level



Color Customization, MOQ 50pcs



# PORTABLE X-RAY MACHINE

YJ-PX905

YJ-PX9010

Application fields, Emergency room, operating room,  
sports medicine, orthopedics, ICU, Nursing home,  
physical examination, Ambulance, Rural medical visits,  
Field training, Animal husbandry, pet hospital





Applicable to both humans and animals

To the patient and operator with the lowest possible dose




High frequency



Efficient



Clarity



Digital Flat panel Detector 17x 17-inch

human- use or animal-usesystem

compact design

Taking images from multiple angles

optional features:

1. Exposure handswitch
2. Adjustable support bracket
3. Built-in computer system



| Product model                   | YJ-PX905                       | YJ-PX9010                     |
|---------------------------------|--------------------------------|-------------------------------|
| power                           | 450W                           | 900W                          |
| kV                              | 40~90kV                        | 40~90kV                       |
| mA                              | 0.5~5mA                        | 1~10mA                        |
| X-ray exposure time             | 0.1~2S                         | 0.1~2S                        |
| Cooling time                    | Thirty times the exposure time | Sixty times the exposure time |
| focus size                      | 0.8                            | 0.8                           |
| Anode heat capacity             | 7000J                          | 7000J                         |
| Total filtering                 | 1.8mm Al                       | 1.8mm Al                      |
| Power supply method             | Battery                        | Battery                       |
| Remote exposure interface       | RJ11                           | RJ11                          |
| image processing                | Optional                       | Optional                      |
| Working environment temperature | -10°C~40°C                     | -10°C~40°C                    |
| size                            | 225*155*263mm                  | 225*155*263mm                 |
| weight                          | 3.5kg                          | 3.8kg                         |